

CHE 307 Display Quiz 2 (Fittings)

02/12/2020

Flange, blind, 2 x 6-inch, standard 125 lb., cast iron



Flange, companion, 1-1/2 x 5-inch, 150 lb., welding neck, 304 SS.



Flange, floor, 3/4 x 3-1/2-inch, threaded, galvanized.



Union, 1/4-inch, aluminum.



Cross, Pyrex, 2-inch.



Coupling, reducing, 2 x 3/4-inch, threaded, galvanized.



Coupling, straight, 1/2-inch, threaded, black iron.



Bushing, 1 x 3/4-inch, threaded, black iron.



Plug, 1-1/2-inch, threaded, black iron.



Cap, 1-inch, threaded, aluminum.



Elbow, street, 1-inch, threaded, galvanized.



Nipple, close, threaded, 1-inch.



Tee, reducing, 1-1/2 x 1-1/2 x 1-inch, threaded, black iron.



Cross, 1-inch, threaded, galvanized.



Tee, 1-1/2-inch, sweat ends, copper.



Connector, 1-inch, screwed to sweat, copper



Elbow, 45 degrees, 3/4-inch, galvanized, threaded



Elbow, 1-inch, screwed to sweat, brass.



Elbow, 1/8-inch pipe to 1/4-inch tubing, flare type, brass.



1/4-inch flare nut



Elbow, 1/4 -inch pipe to 1/4-inch plastic tubing, ferrule type, brass.



Connector, 1/4-inch pipe to 1/2-inch rubber tubing, stainless steel



D2 Page 8

Swing joint, 3/4-inch, brass.



Elbow 1-1/4-inch, aluminum, with 1-1/4-inch male pipe side outlet.



D2 Page 9

Adapter, 3/4-inch pipe to 5/8-inch hose, male ends, brass



Tee, 1/2-inch, FMF, threaded ends, brass



Tee, 3/4-inch, flanged ends, brass



D2 Page 10

Elbow, 1-inch, sweat ends, copper



ProPress Copper Coupling Connection 3/4-inch x 3/4-inch pressed fitting with o-ring seal.200PSI@250F



PEX copper coupling and tubing 1/2-inch 100PSI@160F



Male Adaptor, 1-inch NPT Thread to 1-1/2-inch **Sanitary Tri-Clamp**, with Teflon gasket

