

CHE 307 Display 3 (General)

02/12/2020

Syphon, steam, 1/4-inch, threaded, black iron



Indicator, sight-flow, 3/4-inch, brass, threaded



Strainer, steam, 1/2-inch, threaded galvanized



Steam trap, bucket type, 1/2-inch, steel



Steam trap, bellows type, 3/4-inch, brass



Thermowell, 3/4-inch, for Weston thermometer, SS



Thermometer, bimetallic, 1/2-inch mounting threads, range 50-400 degrees F



Thermometer, industrial armored type, with thermowell, range 40-110 degrees F



Bucket for bucket type steam trap



Wrench, box end, 1 1/16 x 15/16-inch



Wrench, open end, 3/4 x 7/8-inch



Phillips screwdriver



Hex Key wrench, 3/16-inch



Pipe clamp, one hole, 3/4-inch



D3 Page 5

Gage, pressure, range 0-100 psig, 1 lb. increments, recessed panel mounting, 1/4-inch threaded



Gage, pressure range 0-60 psig, 1 lb. increments, flush panel mounting, 1/4-inch threaded



Filter, instrument air



D3 Page 6

Inside pipe wrench, 1-inch



Bolt, machine, 1/2-inch, square head, steel



Bolt, machine, 3/8-inch, hex head, cadmium plated



D3 Page 7

Stud, 1/2 x 2-inch, brass



Screw, machine, 3/8-inch, round head, brass



Screw, machine, 1/4-inch, countersunk flat head, steel



Wound Primary Current Transformer, 10:5 Current Ratio

